

Dispersive Signal Technology

A Revolutionary New Touch Technology from 3M

Dispersive Signal Technology provides a new, innovative technology choice for retail, point of sale (POS), finance, hospitality, signage and gaming applications. Setting new standards for the touch industry, this patented technology delivers exceptional optics, extreme durability, and stylus support combined with great accuracy and fast touch response.

Dispersive Signal Technology works on the premise of measuring the mechanical energy (bending waves) within a glass substrate that is created when someone touches the surface of the glass. Sensors, generally placed on the backside of the glass, convert this energy into electrical signals. Using advanced proprietary signal processing algorithms, the Dispersive Signal Technology system determines the location of the touch, taking into account the profile of the bending wave, glass dispersion effects, and other characteristics of the substrate.

The Difference is “Through” the Substrate

Where other touch technologies distribute a field across the front surface of the touch screen and rely on a touch to interrupt the field, Dispersive Signal Technology waits passively for a signal created by a touch. This fundamentally different approach means that contaminants, such as dirt, grease, and solids, can accumulate on the surface and around the edge of the screen without a significant effect on the performance of the touch screen. It also scales readily for large size displays, using the same electronics for all sizes of glass. Furthermore, surface damage such as scratches or gouges generally will not affect performance, making Dispersive Signal Technology ideal for unsupervised public access as well as food service and gaming applications.

Exceptional Optics, Contaminant Resistance, and Much More

Since the substrate is pure glass with no metallic coatings, ridge reflectors, or opto-electronic components, Dispersive Signal Technology provides exceptional optical clarity and light transmission, and can be sealed to prevent contaminants from entering the touch screen enclosure, protecting the display and other internal components.



Key Benefits

- Exceptional Optical Characteristics
- Stylus Support
- Enhanced Palm Rejection
- Scalable
- Contaminant Resistant
- Durable Glass Surface
- Performance Generally Not Affected by Surface Damage, including Scratches

Stylus Support

Since Dispersive Signal Technology measures the vibration created by a touch, nearly any object – finger, prosthetic device, pen, credit card, most gloves – can be used to activate the touch screen. This is particularly useful in retail and restaurant applications where the user may use different types of objects to operate the touch screen.

Enhanced Palm Rejection

Dispersive Signal Technology also provides enhanced palm rejection – a user can rest their hand or other objects on the touch screen during use without activating the touch screen unless they tap the surface. This unique capability is universally beneficial, but particularly useful for signature capture, bartop gaming, and kiosk applications, where users tend to rest the edge their palm against the surface of the touch screen. Enhanced palm rejection is one of many break-through capabilities 3M plans to deliver with Dispersive Signal Technology to innovatively change the touch screen industry.

Sophisticated, Yet Fast

Although Dispersive Signal Technology uses intricate, proprietary software algorithms, its touch response time rivals the fastest in the industry. In retail, POS, and entertainment applications, where users are particularly adept and quick, the faster the response of the touch screen, the more transactions occur per hour increasing productivity or profitability, and customer satisfaction.

The Innovation Continues


The fundamentally different approach of Dispersive Signal Technology promises to further expand the opportunities to use touch screen technology. It brings together the unique combination of exceptional optics with stylus support and contaminant resistance, never before seen in the touch industry. Adopters of Dispersive Signal Technology will not only benefit from all the capabilities they've come to expect with other touch technologies, they will realize new benefits from advanced features such as enhanced palm rejection – the first of many innovative break-throughs that 3M provides with Dispersive Signal Technology.

Dispersion Explained


Dispersion is the phenomenon that the velocity of a bending wave propagating through solid material is dependent upon that wave's frequency. A vibration caused by a touch generates a number of bending waves within the substrate, all at different frequencies. Because of dispersion, these bending waves propagate out to the edges of the glass at different speeds rather than in a unified wave front. The sensors at the edges sense the high frequency waves first – the lower frequency waves arrive later, with the sensors receiving a formation of waves that resemble nothing like the original pulse. This smearing effect is compounded by the reflections off the internal surfaces of the glass substrate. The net result is a seemingly chaotic mass of waves all interfering with one another throughout the substrate.

3M has successfully harnessed this technology by developing a set of proprietary algorithms that accounts for the dispersion effect, gleaned from the mass of chaos a clear, precise touch location. These algorithms are the result of extensive R&D effort providing a highly accurate and sensitive solution. No other touch technology works quite this way.


Graphic Representation of Bending Wave Effect on Glass Substrate




Initial Touch Down



Progressing Dispersion
with the Beginning of
Reflection Effects



Highly Complex Dispersion
Pattern with Reflections



Post-Algorithm Pattern

NOTICE: Given the variety of factors that can affect the use and performance of a 3M Touch Systems Product (the "Product"), including that solid state equipment has operation characteristics different from electromechanical equipment, some of which factors are uniquely within User's knowledge and control, it is essential that User evaluate the product and software to determine whether it is suitable for User's particular purpose and suitable for User's method of application. 3M Touch Systems' statements, engineering/technical information, and recommendations are provided for User's convenience, but their accuracy or completeness is not warranted. 3M Touch Systems products and software are not specifically designed for use in medical devices as defined by United States federal law. 3M Touch Systems products and software should not be used in such applications without 3M Touch Systems' express written consent. User should contact its sales representative if User's opportunity involves a medical device application.

IMPORTANT NOTICE TO PURCHASER: Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. **3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose.** User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software media or to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. **3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted. (7/02)**



3M Touch Systems
3M Optical Systems Division
300 Griffin Brook Park Drive
Methuen, MA 01844 USA
1-866-407-6666

Worldwide Manufacturing Plants:
Methuen, Massachusetts
Milwaukee, Wisconsin
Vancouver, BC Canada

For more information on 3M touch products,
visit 3Mtouch.com