

Features:

- 1U Rackmount Single Rail easy to install and use
- 15" LCD Bright Active Matrix TFT Display
- OSD function (On Screen Display) for LCD display
- Durable Notebook keyboards with Touchpad
- Panel protected by tempered glass
- LCD AutoShut off in closed position
- Separate rail design, can be installed by one person

Specifications

Model Number PL150U-RM-XAXR

Display Size 15"

Dimensions 447.5x482x44mm/17.6x19.0x1.7in

Net Weight 10.0Kg / 22.0Lb
Panel Type Active Matrix TFT LCD

Resolution Capabilities Maximum Resolution up to 1024X768

(XGA)

Pixel Pitch Supports 0.297mm x0.297mm Viewing Angle (CR>10) Right-Left view 130°(Typ), Up-Down View 100°(Typ)

Contrast Ratio 400:1

Brightness White 250cd/m2 (Center 1 point Typ)

Back Light Dual Lamps for Back Light
Supported Colors 16M Colors (6-bit with FRC)
Response Time Rising Time 5ms, Decay Time 11ms

Operating System

Operating System

Dos, Windows (3.1, 9x, 2000, NT4, ME, XP, 2003 Server) Linux, Novell 3.12-6, HP

UX

System Cables VGA+2xPS/2 cable

Keyboard Mouse 106 key PS/2 keyboard with touch pad

Sync 45~80KHZ

Power Source 100-240 VAC input Power Consumption 16W, 10.41W for Panel

Temperature Operate $0^{\circ} \sim 50^{\circ} \text{C} / 32^{\circ} \sim 122^{\circ} \text{F}$,

Storage-20°~ 60°C / -4°~ 140°F

Humidity 10%~90%RH

Keyboard Language Standard USA. Options for (UK, German,

French, Spanish, Italian, Portuguese, Dutch, Swiss, Belgium, Swedish, Norwegian, Danish, Japan, Taiwan)

Certification CE/FCC, UL













